

Acrylic Letters / Logos

Flat, Smooth Interior Surface

Acrylic letters with NO hardware.

**Tools Required:** Spacing Guide, level, masking tape, tape measure, cleaning cloth, optional adhesive and/or VHB tape.



Video



**1. CLEAN Mounting Surface**

Clean and prepare mounting surface before starting your install.

**Tip:** Surface should be flat, clean and free of excess dust or moisture.

**2. POSITION and Secure Guide**

A Spacing or Stencil Guide are recommended to properly install fat letters. Layout, level and securely tape your guide flat to mounting surface. Check spelling, spacing and kerning of letters on guide.



Full **Stencil Guide** - for smaller letters.



**Split Stencil** Guide for larger letters & logos.



**3. APPLY Adhesive / Tape to Letters**

Plain letters can be installed with a quality VHB Tape, adhesive or a combination of the two. Be sure to use a quality VHB tape and adhesive, such as Epoxy, that will bond to the plastic and your mounting surface. Install one letter at a time.



**4. TAPE Letters to Secure**


Using long strips of tape, securely tape letters to wall using guide. Stand back and perform a visual check to make sure letters are straight. Lift tape and reposition letters as needed to set straight.



Perform a final check, from a distance, to insure proper spelling & spacing.

**5. PRESS Letters to Set**

After letters are aligned straight, apply additional pressure to the face of each separate letter. VHB tape requires **pressure** to properly set. Press letters hard with fingers, roller or flat board to fully set the VHB tape. Remove paper guide after letters are set.



**6. REMOVE Masking Tape & Face Masking.**

After adhesive sets (letters do not move), remove masking tape from letters. Finally, remove protective letter masking from letter faces. Clean off letter faces as needed.